

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 304

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish	径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish	径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.399	SD	65	× 4~6m	26.4	PM	270	× 4~6m	457	TM
9	× 4~6	0.505	"	70	× 4~6	30.6	"	280	× 4~6	492	"
10	× 4~6	0.623	"	75	× 4~6	35.2	"	290	× 4~6	527	"
12	× 4~6	0.897	"	80	× 4~6	40.0	"	300	× 3 up	564	"
13	× 4~6	1.05	"	85	× 4~6	45.3	"	310	× 3 up	602	"
14	× 4~6	1.22	"	90	× 4~6	50.7	"	320	× 3 up	642	"
16	× 4~6	1.61	PM	95	× 4~6	56.5	"	330	× 3 up	682	"
18	× 4~6	2.03	"	100	× 4~6	62.6	"	340	× 3 up	724	"
19	× 4~6	2.27	"	105	× 4~6	69.0	"	350	× 3 up	767	"
20	× 4~6	2.51	"	110	× 4~6	75.7	"	360	× 3 up	812	"
22	× 4~6	3.03	"	115	× 4~6	82.7	"	380	× 3 up	904	"
24	× 4~6	3.61	"	120	× 4~6	90.1	"	400	× 3 up	1002	"
25	× 4~6	3.92	"	125	× 4~6	97.7	"	410	× 2 up	1052	"
26	× 4~6	4.25	"	130	× 4~6	106	"	420	× 2 up	1104	"
28	× 4~6	4.93	"	135	× 4~6	114	"	450	× 2 up	1267	"
30	× 4~6	5.65	"	140	× 4~6	123	"	460	× 2 up	1324	"
32	× 4~6	6.43	"	145	× 4~6	132	"	480	× 2 up	1441	"
34	× 4~6	7.25	"	150	× 4~6	141	"	500	× 2 up	1563	"
35	× 4~6	7.68	"	155	× 4~6	152	"	530	× 2 up	1755	"
36	× 4~6	8.13	"	160	× 4~6	161	"	560	× 2 up	1960	"
38	× 4~6	9.06	"	170	× 4~6	182	TR	610	× 2 up	2325	"
40	× 4~6	10.0	"	180	× 4~6	204	"				
42	× 4~6	11.1	"	190	× 4~6	227	"				
44	× 4~6	12.1	"	200	× 4~6	252	"				
45	× 4~6	12.7	"	210	× 4~6	277	"				
46	× 4~6	13.3	"	220	× 4~6	304	"				
48	× 4~6	14.4	"	230	× 4~6	332	TM				
50	× 4~6	15.6	"	240	× 4~6	362	"				
55	× 4~6	18.9	"	250	× 4~6	392	"				
60	× 4~6	22.5	"	260	× 4~6	424	"				

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)
TR: ラフターン (Rough Turned)

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 304L

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
10	× 4~6m	0.623	SD
13	× 4~6	1.05	〃
14	× 4~6	1.22	〃
16	× 4~6	1.59	〃
19	× 4~6	2.27	PM
20	× 4~6	2.51	〃
22	× 4~6	3.03	〃
25	× 4~6	3.92	〃
28	× 4~6	4.93	〃
30	× 4~6	5.65	〃
32	× 4~6	6.43	〃
35	× 4~6	7.68	〃
36	× 4~6	8.13	〃
38	× 4~6	9.06	〃
40	× 4~6	10.0	〃
42	× 4~6	11.1	〃
45	× 4~6	12.7	〃
50	× 4~6	15.6	〃
55	× 4~6	18.9	〃
60	× 4~6	22.5	〃
65	× 4~6	26.4	〃
70	× 4~6	30.6	〃
75	× 4~6	35.2	〃
80	× 4~6	40.0	〃
85	× 4~6	45.3	〃
90	× 4~6	50.7	〃
95	× 4~6	56.5	〃
100	× 4~6	62.6	〃
110	× 4~6	75.7	〃
120	× 4~6	90.1	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 303

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
10	× 4~6m	0.623	SD
13	× 4~6	1.05	〃
14	× 4~6	1.22	〃
16	× 4~6	1.59	〃
18	× 4~6	2.03	PM
19	× 4~6	2.27	〃
20	× 4~6	2.51	〃
22	× 4~6	3.03	〃
24	× 4~6	3.61	〃
25	× 4~6	3.92	〃
26	× 4~6	4.25	〃
28	× 4~6	4.93	〃
30	× 4~6	5.65	〃
32	× 4~6	6.43	〃
34	× 4~6	7.25	〃
35	× 4~6	7.68	〃
36	× 4~6	8.13	〃
38	× 4~6	9.06	〃
40	× 4~6	10.0	〃
42	× 4~6	11.1	〃
45	× 4~6	12.7	〃
46	× 4~6	13.3	〃
48	× 4~6	14.4	〃
50	× 4~6	15.6	〃
55	× 4~6	18.9	〃
60	× 4~6	22.5	〃
65	× 4~6	26.4	〃
70	× 4~6	30.6	〃
75	× 4~6	35.2	〃
80	× 4~6	40.0	〃
85	× 4~6	45.3	〃
90	× 4~6	50.7	〃
95	× 4~6m	56.5	PM
100	× 4~6	62.6	〃
110	× 4~6	75.7	〃
120	× 4~6	90.1	〃
130	× 4~6	106	〃
140	× 4~6	123	〃
150	× 4~6	141	〃
160	× 4~6	161	〃
170	× 4~6	182	TM
180	× 4~6	204	〃
190	× 4~6	227	〃
200	× 4~6	252	〃
210	× 4~6	277	〃
220	× 4~6	304	〃
230	× 4~6	332	〃
240	× 4~6	362	〃
250	× 4~6	392	〃
260	× 4~6	424	〃
270	× 4~6	457	〃
280	× 4~6	492	〃
290	× 4~6	527	〃
300	× 3 up	564	〃
320	× 3 up	642	〃
340	× 3 up	724	〃
350	× 3 up	767	〃
370	× 3 up	857	〃
400	× 3 up	1002	〃
420	× 2 up	1104	〃
450	× 2 up	1267	〃
480	× 2 up	1441	〃
500	× 2 up	1563	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 316

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.401	SD
9	× 4~6	0.508	〃
10	× 4~6	0.627	〃
12	× 4~6	0.903	〃
13	× 4~6	1.06	〃
14	× 4~6	1.23	〃
16	× 4~6	1.60	〃
18	× 4~6	2.05	PM
19	× 4~6	2.28	〃
20	× 4~6	2.53	〃
22	× 4~6	3.05	〃
24	× 4~6	3.63	〃
25	× 4~6	3.94	〃
26	× 4~6	4.28	〃
28	× 4~6	4.96	〃
30	× 4~6	5.69	〃
32	× 4~6	6.47	〃
34	× 4~6	7.30	〃
35	× 4~6	7.73	〃
36	× 4~6	8.18	〃
38	× 4~6	9.11	〃
40	× 4~6	10.1	〃
42	× 4~6	11.1	〃
44	× 4~6	12.2	〃
45	× 4~6	12.8	〃
46	× 4~6	13.3	〃
48	× 4~6	14.5	〃
50	× 4~6	15.7	〃
55	× 4~6	19.0	〃
60	× 4~6	22.7	〃
65	× 4~6	26.6	〃
70	× 4~6	30.8	〃
75	× 4~6	35.4	〃

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
80	× 4~6m	40.2	PM
85	× 4~6	45.5	〃
90	× 4~6	51.0	〃
95	× 4~6	56.9	〃
100	× 4~6	63.0	〃
110	× 4~6	76.2	〃
120	× 4~6	90.7	〃
130	× 4~6	107	〃
140	× 4~6	124	〃
150	× 4~6	142	〃
160	× 4~6	162	〃
170	× 4~6	183	TM
180	× 4~6	205	〃
190	× 4~6	229	〃
200	× 4~6	253	〃
210	× 4~6	279	〃
220	× 4~6	306	〃
230	× 4~6	334	〃
240	× 4~6	364	〃
250	× 4~6	395	〃
260	× 4~6	427	〃
270	× 4~6	460	〃
280	× 4~6	495	〃
290	× 4~6	530	〃
300	× 3 up	568	〃
320	× 3 up	645	〃
350	× 3 up	772	〃
370	× 3 up	862	〃
400	× 3 up	1009	〃
420	× 2 up	1111	〃
450	× 2 up	1275	〃
480	× 2 up	1449	〃
500	× 2 up	1573	〃

SUS 316L

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.401	SD
10	× 4~6	0.627	〃
12	× 4~6	0.903	〃
13	× 4~6	1.06	〃
14	× 4~6	1.23	〃
16	× 4~6	1.60	〃
19	× 4~6	2.28	PM
20	× 4~6	2.53	〃
22	× 4~6	3.05	〃
25	× 4~6	3.94	〃
28	× 4~6	4.96	〃
30	× 4~6	5.69	〃
32	× 4~6	6.47	〃
35	× 4~6	7.73	〃
36	× 4~6	8.18	〃
38	× 4~6	9.11	〃
40	× 4~6	10.1	〃
42	× 4~6	11.1	〃
45	× 4~6	12.8	〃
46	× 4~6	13.3	〃
48	× 4~6	14.5	〃
50	× 4~6	15.7	〃
55	× 4~6	19.0	〃
60	× 4~6	22.7	〃
65	× 4~6	26.6	〃
70	× 4~6	30.8	〃
75	× 4~6	35.4	〃
80	× 4~6	40.2	〃
85	× 4~6	45.5	〃
90	× 4~6	51.0	〃

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
95	× 4~6m	56.9	PM
100	× 4~6	63.0	〃
110	× 4~6	76.2	〃
120	× 4~6	90.7	〃
130	× 4~6	107	〃
140	× 4~6	124	〃
150	× 4~6	142	〃
160	× 4~6	162	〃
170	× 4~6	183	TM
180	× 4~6	205	〃
190	× 4~6	229	〃
200	× 4~6	253	〃
210	× 4~6	279	〃
220	× 4~6	306	〃
230	× 4~6	334	〃
240	× 4~6	364	〃
250	× 4~6	395	〃
260	× 4~6	427	〃
280	× 4~6	495	〃
300	× 3 up	568	〃
350	× 3 up	772	〃
400	× 3 up	1009	〃
420	× 2 up	1111	〃
450	× 2 up	1275	〃
480	× 2 up	1449	〃
500	× 2 up	1573	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 310S

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.401	SD
10	× 4~6	0.627	〃
13	× 4~6	1.06	〃
16	× 4~6	1.60	〃
19	× 4~6	2.28	PM
20	× 4~6	2.53	〃
22	× 4~6	3.05	〃
25	× 4~6	3.94	〃
28	× 4~6	4.96	〃
30	× 4~6	5.69	〃
32	× 4~6	6.47	〃
35	× 4~6	7.73	〃
36	× 4~6	8.18	〃
38	× 4~6	9.11	〃
40	× 4~6	10.1	〃
42	× 4~6	11.1	〃
45	× 4~6	12.8	〃
46	× 4~6	13.3	〃
50	× 4~6	15.7	〃
55	× 4~6	19.0	〃
60	× 4~6	22.7	〃
65	× 4~6	26.6	〃
70	× 4~6	30.8	〃
75	× 4~6	35.4	〃
80	× 4~6	40.2	〃
85	× 4~6	45.5	〃
90	× 4~6	51.0	〃
95	× 4~6	56.9	〃
100	× 4~6	63.0	〃
110	× 4~6	76.2	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 321

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
120	× 4~6m	90.7	PM
130	× 4~6	107	〃
140	× 4~6	124	〃
150	× 4~6	142	〃
160	× 4~6	162	〃
170	× 4~6	183	TM
180	× 4~6	205	〃
200	× 4~6	253	〃
250	× 4~6	395	〃
16	× 4~6m	1.59	SD
19	× 4~6	2.27	PM
22	× 4~6	3.03	〃
26	× 4~6	4.25	〃
28	× 4~6	4.93	〃
30	× 4~6	5.65	〃
32	× 4~6	6.43	〃
34	× 4~6	7.25	〃
35	× 4~6	7.68	〃
38	× 4~6	9.06	〃
40	× 4~6	10.0	〃
42	× 4~6	11.1	〃
45	× 4~6	12.7	〃
50	× 4~6	15.6	〃
55	× 4~6	18.9	〃
60	× 4~6	22.5	〃
65	× 4~6	26.4	〃
70	× 4~6	30.6	〃
75	× 4~6	35.2	〃
80	× 4~6	40.0	〃
90	× 4~6	50.7	〃
100	× 4~6	62.6	〃
110	× 4~6	75.7	〃
120	× 4~6	90.1	〃
130	× 4~6	106	〃
140	× 4~6	123	〃
150	× 4~6	141	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)

SUS 304N2

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
9	× 4~6m	0.505	SD
13	× 4~6	1.05	〃
16	× 4~6	1.59	〃
19	× 4~6	2.27	PM
20	× 4~6	2.51	〃
22	× 4~6	3.03	〃
25	× 4~6	3.92	〃
28	× 4~6	4.93	〃
30	× 4~6	5.65	〃
32	× 4~6	6.43	〃
35	× 4~6	7.68	〃
38	× 4~6	9.06	〃
40	× 4~6	10.0	〃
45	× 4~6	12.7	〃
50	× 4~6	15.6	〃
55	× 4~6	18.9	〃
60	× 4~6	22.5	〃
65	× 4~6	26.4	〃
70	× 4~6	30.6	〃
75	× 4~6	35.2	〃
80	× 4~6	40.0	〃
85	× 4~6	45.3	〃
90	× 4~6	50.7	〃
100	× 4~6	62.6	〃
110	× 4~6	75.7	〃
120	× 4~6	90.1	〃
130	× 4~6	105	〃
140	× 4~6	123	〃
150	× 4~6	141	〃
160	× 4~6	161	〃
170	× 4~6	182	TM
180	× 4~6	204	〃
190	× 4~6	227	〃
200	× 4~6	252	〃
210	× 4~6	277	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 329J1

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
13	× 4~6m	1.05	PM
16	× 4~6	1.59	SD/PM
19	× 4~6	2.27	PM
22	× 4~6	3.03	〃
26	× 4~6	4.25	〃
28	× 4~6	4.93	〃
32	× 4~6	6.43	〃
36	× 4~6	8.13	〃
38	× 4~6	9.06	〃
40	× 4~6	10.0	〃
42	× 4~6	11.1	〃
46	× 4~6	13.3	〃
50	× 4~6	15.6	〃
55	× 4~6	18.9	〃
60	× 4~6	22.5	〃
65	× 4~6	26.4	〃
70	× 4~6	30.6	〃
75	× 4~6	35.2	〃
80	× 4~6	40.0	〃
90	× 4~6	50.7	〃
100	× 4~6	62.6	〃
110	× 4~6	75.7	〃
120	× 4~6	90.1	〃
130	× 4~6	106	〃
150	× 4~6	141	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 329J4L

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
16	× 4~6m	1.61	PM
30	× 4~6	5.65	〃
50	× 4~6	15.6	〃
80	× 4~6	40.0	〃
100	× 4~6	62.6	〃
120	× 4~6	90.1	〃
150	× 4~6	141	〃
200	× 4~6	252	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 630

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
10	× 4~6m	0.611	PM
13	× 4~6	1.03	〃
16	× 4~6	1.58	〃
19	× 4~6	2.22	〃
20	× 4~6	2.46	〃
22	× 4~6	2.98	〃
25	× 4~6	3.84	〃
26	× 4~6	4.17	〃
28	× 4~6	4.83	〃
30	× 4~6	5.55	〃
32	× 4~6	6.31	〃
34	× 4~6	7.12	〃
36	× 4~6	7.97	〃
38	× 4~6	8.88	〃
40	× 4~6	9.84	〃
42	× 4~6	10.8	〃
45	× 4~6	12.4	〃
46	× 4~6	13.0	〃
50	× 4~6	15.3	〃
55	× 4~6	18.6	〃
60	× 4~6	22.1	〃
65	× 4~6	25.9	〃
70	× 4~6	30.0	〃
75	× 4~6	34.5	〃
80	× 4~6	39.2	〃
85	× 4~6	44.4	〃
90	× 4~6	49.8	〃
95	× 4~6	55.4	〃
100	× 4~6	61.4	〃
110	× 4~6	74.3	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
120	× 4~6m	88.4	PM
130	× 4~6	104	〃
140	× 4~6	121	〃
150	× 4~6	138	〃
160	× 4~6	158	〃
170	× 4~6	179	TM
180	× 4~6	200	〃
190	× 4~6	223	〃
200	× 4~6	247	〃
250	× 4~6	383	〃

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 403

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.390	SD
9	× 4~6	0.493	〃
10	× 4~6	0.609	〃
12	× 4~6	0.877	〃
13	× 4~6	1.03	〃
14	× 4~6	1.19	〃
16	× 4~6	1.56	〃
18	× 4~6	1.99	PM
19	× 4~6	2.21	〃
20	× 4~6	2.45	〃
22	× 4~6	2.97	〃
24	× 4~6	3.53	〃
25	× 4~6	3.83	〃
26	× 4~6	4.15	〃
28	× 4~6	4.82	〃
30	× 4~6	5.52	〃
32	× 4~6	6.28	〃
34	× 4~6	7.09	〃
35	× 4~6	7.51	〃
36	× 4~6	7.94	〃
38	× 4~6	8.85	〃
40	× 4~6	9.80	〃
42	× 4~6	10.8	〃
44	× 4~6	11.8	〃
45	× 4~6	12.4	〃
46	× 4~6	13.0	〃
48	× 4~6	14.1	〃
50	× 4~6	15.3	〃
55	× 4~6	18.5	〃
60	× 4~6	22.0	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 420J2

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.390	SD
9	× 4~6	0.493	〃
10	× 4~6	0.609	〃
12	× 4~6	0.877	〃
13	× 4~6	1.03	〃
14	× 4~6	1.19	〃
16	× 4~6	1.56	〃
18	× 4~6	1.99	PM
19	× 4~6	2.21	〃
20	× 4~6	2.45	〃
22	× 4~6	2.97	〃
24	× 4~6	3.53	〃
25	× 4~6	3.83	〃
26	× 4~6	4.15	〃
28	× 4~6	4.82	〃
30	× 4~6	5.52	〃
32	× 4~6	6.28	〃
34	× 4~6	7.09	〃
36	× 4~6	7.94	〃
38	× 4~6	8.85	〃
40	× 4~6	9.80	〃
42	× 4~6	10.8	〃
44	× 4~6	11.8	〃
45	× 4~6	12.4	〃
46	× 4~6	13.0	〃
48	× 4~6	14.1	〃
50	× 4~6	15.3	〃
55	× 4~6	18.5	〃
60	× 4~6	22.0	〃
65	× 4~6	25.8	〃
70	× 4~6	29.9	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)

丸棒 (ステンレス鋼棒)

Stainless Steel Round Bars

SUS 416

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
16	× 4~6m	1.57	PM
18	× 4~6	1.99	〃
20	× 4~6	2.45	〃
22	× 4~6	2.97	〃
24	× 4~6	3.53	〃
25	× 4~6	3.83	〃
26	× 4~6	4.15	〃
28	× 4~6	4.82	〃
30	× 4~6	5.52	〃
32	× 4~6	6.28	〃
34	× 4~6	7.09	〃
36	× 4~6	7.94	〃
38	× 4~6	8.85	〃
40	× 4~6	9.80	〃
42	× 4~6	10.8	〃
46	× 4~6	13.0	〃
48	× 4~6	14.1	〃
50	× 4~6	15.3	〃
55	× 4~6	18.5	〃
60	× 4~6	22.0	〃
65	× 4~6	25.8	〃
70	× 4~6	29.9	〃
75	× 4~6	34.4	〃
80	× 4~6	39.1	〃
85	× 4~6	44.2	〃
90	× 4~6	49.6	〃
95	× 4~6	55.2	〃
100	× 4~6	61.2	〃
110	× 4~6	74.0	〃
120	× 4~6	88.0	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SUS 440C

径 Dia. (mm)	× 長さ Length (m)	質量 Weight (kg/m)	表面仕様 Finish
8	× 4~6m	0.391	SD
10	× 4~6	0.611	〃
13	× 4~6	1.03	〃
16	× 4~6	1.56	〃
19	× 4~6	2.22	PM
20	× 4~6	2.46	〃
22	× 4~6	2.98	〃
25	× 4~6	3.84	〃
26	× 4~6	4.17	〃
28	× 4~6	4.83	〃
30	× 4~6	5.55	〃
32	× 4~6	6.31	〃
36	× 4~6	7.97	〃
38	× 4~6	8.88	〃
40	× 4~6	9.84	〃
42	× 4~6	10.8	〃
45	× 4~6	12.4	〃
46	× 4~6	13.0	〃
50	× 4~6	15.3	〃
55	× 4~6	18.6	〃
60	× 4~6	22.1	〃
65	× 4~6	25.9	〃
70	× 4~6	30.0	〃
75	× 4~6	34.5	〃
80	× 4~6	39.2	〃
85	× 4~6	44.4	〃
90	× 4~6	49.8	〃
95	× 4~6	55.4	〃
100	× 4~6	61.4	〃
110	× 4~6	74.3	〃

JIS G 4303 ステンレス鋼棒
Stainless Steel Round Bars

SD: 酸洗 (Pickled)
PM: ピーリング (Smooth Turned)
TM: ターニング (Rough Turned)

CFB

Cold Drawn Round Bars

SUS 304

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差	
			h9	h10
6	× 4000	0.224	○	
8	× 4000	0.399	○	
9	× 4000	0.505	○	
9.52	× 4000	0.564	○	
10	× 4000	0.623	○	
11	× 4000	0.754	○	
12	× 4000	0.897	○	
12.7	× 4000	1.00	○	
13	× 4000	1.05	○	
14	× 4000	1.22	○	
15	× 4000	1.40	○	
15.87	× 4000	1.57	○	
16	× 4000	1.59	○	
17	× 4000	1.80	○	
18	× 4000	2.02	○	
	5000	2.02	○	
19	× 4000	2.25	○	
	5000	2.25	○	
19.05	× 5000	2.26	○	
20	× 4000	2.49	○	
	5000	2.49	○	
21	× 4000	2.75	○	
22	× 4000	3.01	○	
	5000	3.01	○	
23	× 4000	3.29	○	
	5000	3.29	○	
24	× 4000	3.59	○	
	5000	3.59	○	
25	× 4000	3.89	○	
	5000	3.89	○	

SUS 303

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差	
			h9	h10
25.4	× 5000	4.02	○	
26	× 4000	4.21	○	
	6000	4.21	○	
28	× 4000	4.88	○	
	6000	4.88	○	
30	× 4000	5.61	○	
	6000	5.61	○	
32	× 6000	6.38	○	
35	× 6000	7.63	○	
36	× 6000	8.07	○	
38	× 6000	8.99	○	
40	× 6000	9.97	○	
42	× 6000	11.0	○	
45	× 6000	12.6	○	
50	× 6000	15.6	○	
55	× 6000	18.8	○	
60	× 6000	22.4	○	
65	× 6000	26.3	○	
70	× 6000	30.5	○	
75	× 6000	35.0	○	
80	× 6000	39.9	○	○
85	× 6000	45.0	○	○
90	× 6000	50.5	○	○
95	× 6000	56.2	○	○
100	× 6000	62.3	○	○

SUS 316

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差	
			h9	h10
8	× 4000	0.401	○	
9	× 4000	0.507	○	
10	× 4000	0.627	○	
12	× 4000	0.903	○	
13	× 4000	1.06	○	
14	× 4000	1.23	○	
15	× 4000	1.41	○	
16	× 4000	1.60	○	
17	× 4000	1.81	○	
18	× 5000	2.03	○	
19	× 5000	2.26	○	
20	× 5000	2.51	○	
22	× 5000	3.03	○	
24	× 5000	3.61	○	
25	× 5000	3.92	○	
28	× 6000	4.24	○	
30	× 6000	5.64	○	
32	× 6000	6.42	○	
35	× 6000	7.68	○	
40	× 6000	10.0	○	
45	× 6000	12.7	○	
50	× 6000	15.7	○	

センターレス

Centerless Ground Round Bars

SUS 304

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
3	× 2000	0.055	+0~-0.010
4	× 2000	0.099	+0~-0.012
5	× 2000	0.156	
6	× 2000	0.224	
7	× 2000	0.305	+0~-0.015
8	× 2000	0.399	
9	× 2000	0.504	
10	× 2000	0.623	
11	× 2000	0.754	+0~-0.018
12	× 2000	0.897	
13	× 2000	1.052	
14	× 2000	1.221	
15	× 2000	1.401	
16	× 2000	1.594	
17	× 2000	1.800	
18	× 2000	2.018	
19	× 2000	2.248	+0~-0.021
20	× 2000	2.491	
22	× 2000	3.014	
24	× 2000	3.587	
25	× 2000	3.893	
26	× 2000	4.210	
28	× 2000	4.883	
30	× 2000	5.605	+0~-0.025
35	× 2000	7.630	
40	× 2000	9.965	
45	× 2000	12.6	
50	× 2000	15.6	

h7公差

SUS 303

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
3	× 2500	0.055	+0~-0.010
4	× 2500	0.099	+0~-0.012
5	× 2500	0.156	
6	× 2500	0.224	
7	× 2500	0.305	+0~-0.015
8	× 2500	0.399	
9	× 2500	0.504	
10	× 2500	0.623	
11	× 2500	0.754	+0~-0.018
12	× 2500	0.897	
13	× 2500	1.052	
14	× 2500	1.221	
15	× 2500	1.401	
16	× 2500	1.594	
17	× 2500	1.800	
18	× 2500	2.018	
19	× 2500	2.248	+0~-0.021
20	× 2500	2.491	
22	× 2500	3.014	
24	× 2500	3.587	
25	× 2500	3.893	
26	× 2100	4.210	
28	× 2100	4.883	
30	× 2100	5.605	+0~-0.025

SUS 316

径 Dia. (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
4	× 2200	0.100	+0~-0.012
6	× 2200	0.226	
8	× 2200	0.401	+0~-0.015
10	× 2200	0.627	
11	× 2200	0.758	+0~-0.018
12	× 2200	0.903	
13	× 2200	1.059	
14	× 2200	1.228	
15	× 2200	1.410	
16	× 2200	1.604	
18	× 2200	2.031	
19	× 2200	2.263	+0~-0.021
20	× 2200	2.507	
22	× 2200	3.033	
30	× 2200	5.641	

h7公差

六角棒

Cold Finished Stainless Steel Hexagonal Bars

SUS 304

対辺 Subtense (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
8	× 4000	0.439	+0~-0.15
9	× 4000	0.556	
10	× 4000	0.687	
12	× 4000	0.989	+0~-0.18
13	× 4000	1.16	
14	× 4000	1.35	
17	× 4000	1.98	
19	× 4000	2.48	+0~-0.21
21	× 4000	3.03	
22	× 4000	3.32	
23	× 4000	3.63	
24	× 4000	3.96	
26	× 4000	4.64	
27	× 4000	5.01	
29	× 4000	5.78	
30	× 4000	6.18	
32	× 4000	7.03	+0~-0.25
35	× 4000	8.41	
36	× 4000	8.90	
38	× 4000	9.92	
41	× 4000	11.5	
46	× 4000	14.5	
50	× 4000	17.2	
54	× 4000	20.0	+0~-0.30
55	× 4000	20.8	
58	× 4000	23.1	
60	× 4000	24.7	
63	× 4000	27.3	
65	× 4000	29.0	
70	× 4000	33.6	

JIS G 4318 冷間仕上ステンレス鋼棒
Cold Finished Stainless Steel Bars

SUS 303

対辺 Subtense (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
8	× 4000	0.439	+0~-0.15
10	× 4000	0.687	
12	× 4000	0.989	+0~-0.18
13	× 4000	1.16	
14	× 4000	1.35	
17	× 4000	1.98	
19	× 4000	2.48	+0~-0.21
21	× 4000	3.03	
22	× 4000	3.32	
23	× 4000	3.63	
24	× 4000	3.96	
26	× 4000	4.64	
27	× 4000	5.01	
29	× 4000	5.78	
30	× 4000	6.18	
32	× 4000	7.03	+0~-0.25
35	× 4000	8.41	
36	× 4000	8.90	
38	× 4000	9.92	
41	× 4000	11.5	

JIS G 4318 冷間仕上ステンレス鋼棒
Cold Finished Stainless Steel Bars

SUS 316

対辺 Subtense (mm)	× 長さ Length (mm)	質量 Weight (kg/m)	寸法許容差 Tol. (mm)
8	× 4000	0.442	+0~-0.15
10	× 4000	0.691	
12	× 4000	0.995	+0~-0.18
13	× 4000	1.17	
14	× 4000	1.35	
17	× 4000	2.00	
19	× 4000	2.49	+0~-0.21
21	× 4000	3.05	
22	× 4000	3.34	
23	× 4000	3.66	
24	× 4000	3.98	
26	× 4000	4.67	
27	× 4000	5.04	
29	× 4000	5.81	
30	× 4000	6.22	
32	× 4000	7.08	+0~-0.25
35	× 4000	8.47	
36	× 4000	8.95	
38	× 4000	9.98	
41	× 4000	11.6	
46	× 4000	14.6	
50	× 4000	17.3	
54	× 4000	20.1	+0~-0.30
55	× 4000	20.9	

JIS G 4318 冷間仕上ステンレス鋼棒
Cold Finished Stainless Steel Bars

角棒

Stainless Steel Square Bars

SUS 304

寸法名 Size (mm)	長さ Length (mm)	質量 Weight (kg/p)	H O T	C O L D
4 × 4 × 4000		0.508		○
5 × 5 × 4000		0.792		○
6 × 6 × 4000		1.14		○
7 × 7 × 4000		1.56		○
8 × 8 × 4000		2.03		○
9 × 9 × 4000		2.57		○
10 × 10 × 4000		3.17	○	○
12 × 12 × 4000		4.57	○	○
13 × 13 × 4000		5.36	○	○
14 × 14 × 4000		6.22	○	○
15 × 15 × 4000		7.14	○	○
16 × 16 × 4000		8.12	○	○
19 × 19 × 4000		11.5	○	○
20 × 20 × 4000		12.7	○	○
22 × 22 × 4000		15.4	○	○
25 × 25 × 4000		19.8	○	○
26 × 26 × 4000		21.4	○	○
28 × 28 × 4000		24.9	○	○
30 × 30 × 4000		28.6	○	○
32 × 32 × 4000		32.5	○	○
36 × 36 × 4000		41.1	○	○
38 × 38 × 4000		45.8	○	○
40 × 40 × 4000		50.8	○	○
42 × 42 × 4000		56.0	○	
45 × 45 × 4000		64.2	○	○
50 × 50 × 4000		79.3	○	○
55 × 55 × 4000		96.0	○	○
60 × 60 × 4000		114	○	○
65 × 65 × 4000		134	○	○
70 × 70 × 4000		156	○	
75 × 75 × 4000		178	○	
90 × 90 × 4000		257	○	
100×100×4000		317	○	

SUS 316 · 316L(HOT)

寸法名 Size (mm)	長さ Length (mm)	質量 Weight (kg/p)	316	316L
19 × 19 × 4000		11.5	○	○
20 × 20 × 4000		12.8	○	○
22 × 22 × 4000		15.4	○	○
25 × 25 × 4000		20.0	○	○
30 × 30 × 4000		28.7	○	○
32 × 32 × 4000		32.7	○	○
38 × 38 × 4000		46.0	○	○

JIS G 4303 ステンレス鋼棒
Stainless Steel Bars

JIS G 4303 ステンレス鋼棒
Stainless Steel Bars