

外径(mm)	厚み(mm)	長さ	材質・仕様	材質・仕様	材質・仕様	材質・仕様	材質・仕様	材質・仕様
		定尺(mm)	SUS304 BA	SUS316 BA	SUS316L BA	SUS316L BA-S	SUS316L EP-S	SUS316L WEP-S
1.59	1.0φ(内径)	2000		○				
	0.8φ(内径)	2000		○				
2.0	0.5	2000	○					
3.0	0.5	2000	○	○				
	1.0	2000	○	○				
	1	4000	○					
3.18	0.5	2000	○	○				
	0.72	2000	○	○	○	○	○	○
	0.89	2000		○				
4.0	0.5	2000	○	○				
	1.0	2000	○	○				
	1.0	4000	○					
4.8	0.5	2000	○	○				
5.0	0.5	2000	○					
6.0	0.5	2000	○	○				
	1.0	2000	○	○				
	1.0	4000	○	○	○			
	1.5	4000		○				
6.35	0.5	2000		○				
	0.89	2000		○	○			
	0.89	4000		○				
	1.0	2000	○	○	○		○	
	1.0	4000	○	○	○	○	○	○
	1.24	4000	○	○				
	1.65	4000		○				
2.1φ(内径)	2000		○					
8.0	1.0	2000	○	○				
	1.0	4000	○	○	○			
9.53	1.0	2000	○	○	○		○	
	1.0	4000	○	○	○	○	○	○
	1.24	4000	○	○				
	1.65	4000	○	○				

外径(mm)	厚み(mm)	長さ	材質・仕様	材質・仕様	材質・仕様	材質・仕様	材質・仕様	材質・仕様
		定尺(mm)	SUS304 BA	SUS316 BA	SUS316L BA	SUS316L BA-S	SUS316L EP-S	SUS316L WEP-S
10.0	1.0	2000	○	○				
	1.0	4000	○	○	○			
12.0	1.0	2000	○	○				
	1.0	4000	○	○	○			
12.7	1.0	2000	○	○	○		○	
	1.0	4000	○	○	○	○	○	
	1.24	2000	○	○	○			
	1.24	4000	○	○	○	○	○	○
	1.65	4000	○		○			
	2.1	4000		○				
15.88	1.0	4000	○			○		
	1.24	4000		○				
	1.5	4000	○	○				
17.3	1.2	4000				○		
19.05	1.24	2000			○			
	1.24	4000	○	○	○	○	○	○
	1.65	2000			○			
	1.65	4000	○		○		○	
21.7	1.65	4000	○		○	○	○	
25.4	1.65	2000			○			
	1.65	4000	○		○	○	○	○
	2.11	2000			○			
27.2	1.65	4000	○		○	○	○	
34.0	1.65	4000	○		○	○	○	
42.7	1.65	4000	○		○	○	○	
48.6	1.65	4000	○		○	○	○	
60.5	1.65	4000	○		○	○	○	
76.3	2.1	4000				○		
89.1	2.1	4000				○		
114.3	2.1	4000				○		
139.8	2.8	4000				○		
165.2	2.8	4000				○		
216.3	2.8	4000				○		